

# ATTITUDE CEILING FAN



Matt Black

**Installation Locations:**

Indoor and outdoor (provided the fan is fully undercover)  
IP44 Weather Rated

**Recommended Height:**

There should be at least 2.1m between the lowest point of the fan blades and the floor.

**Top of canopy cover to lowest point of the fan :**

Approximately 281mm

**Motor:**

16 Pole, 153mm x 18mm motor  
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

**Motor Housing:**

Materials: Die cast Aluminium

**Available Colours :**

White, Matt Black & Brushed Aluminium

**Blades:**

Sizes: 1320mm (52")  
Materials: Polymer Blades, painted finish  
Blade Pitch: 7°

**Available Blade Colours:**

White, Matt Black & Brushed Aluminium

**Extra Information:**

Introduced into the HPI range in 2012  
User serviceable  
Reversible

**Standard Canopy Cover:**

Suitable for flat and pitched ceilings up to 38°

**Remote Control:**

7 selectable speeds forward & reverse

**Rotational Diameter:**

1320mm (52") blade sweep

**Ceiling to top side of the blade:**

Approximately 243mm

**Weight Including Packaging:**

Complete fan: 8.9kg

**Packaging Dimensions (mm):**

Complete Fan: 634L x 368W x 134H

**Accessories:**

Threaded extension Down Rod 26mm diameter  
T-Hook for ceiling roses  
Universal Mounting Brace

**Warranty**

2 years covering electronic parts  
3 years covering non electronic parts  
5 years covering motor (stator, rotor and windings)

\* All parts can be replaced by the user. Labour for parts installation is not covered by warranty.

**Airflow and Efficiency:**

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

	1	2	3	4	5	6	7
<b>RPMS</b>	193	182	163	150	133	113	55
<b>WATTS</b>	46.2	40.7	33.4	28.6	23.1	17.4	6.6
<b>AIRFLOW<sup>^</sup>:</b> AUS-ES / USA-ES	9523.80 / 12857	8862.70 / 11965	7816.60 / 10552	7261.10 / 9802	6250.20 / 8438	5460.40 / 7372	2569.60 / 3469
<b>EFFICIENCY<sup>^</sup>:</b> AUS-ES / USA-ES	206.14 / 278.29	217.76 / 293.97	234.03 / 315.94	253.88 / 342.74	270.57 / 365.27	313.82 / 423.65	389.33 / 525.60

<sup>^</sup> Airflow measured in Cubic metres/ Hour (CM/HR), Efficiency measured in CM/HR per watt (CMH/W)

# For full warranty details please see Hunter Pacific International's website [www.hunterpacific.com.au](http://www.hunterpacific.com.au)