

Installation Locations:

Indoor & Outdoor (IP33 rated, provided the fan is fully undercover)

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan:

Approximately 540mm

Motor:

16 Pole, 188mm x 20mm motor Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Motor Housing:

Materials: Pressed Steel & Resin

Available Colours:

White & Burnt Copper

Blades:

Sizes: 1320mm (52") Material: PH475 Plastic

Blade Pitch: 12°

Available Blade Colours:

White & Brown

Extra Information:

Introduced into the HPI range in 2007 3 Speed Pull cord Light Adaptable Reversible

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values:

4.3µF & 2.1µF

Rotational Diameter:

1320mm (52") Blade Sweep

Weight Including Packaging:

Complete Fan 1320mm (52"): 13.8kg

Packaging Dimensions (cm):

Complete fan 1320mm (52"): 56L x 39W x 30H

Accessories:

Remote Control
Extension Down Rod 21mm diameter
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses
Universal Mounting Brace

Warranty

2 years "in home" covering major defects 3 Years additional covering motor only (not labour) Remotes -1 year "in home" covering major defects. (receiver and handpiece)

Lights -1 year "in home" covering major defects

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised For USA Energy Star compliance.

Wall control does not come standard	HIGH	MED	LOW
RPMS	215	158	83
WATTS	78.3	42.5	14.9
AIRFLOW^: AUS-ES / USA-ES	11238 / 15171	8100 / 10935	4249 / 5736
EFFICIENCY^: AUS-ES / USA-ES	143.52 / 193.76	190.59 / 257.29	285.17 / 384.98


[^] Airflow measured in Cubic metres/ Hour (CM/HR), Efficiency measured in CM/HR per watt (CMH/W)

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au

MAJESTIC RANGE CEILING FAN LIGHTING



78mm Halogen Light (MAX 100W)



- Cost effective
- Colour-warm white
- Dimmable
- Compact in size


78mm linear Halogen Light globe



GLACIER STYLE GLASS



E27 Light (MAX 2x40W)



- Accepts a variety of lamps, e.g. incandescent, fluorescent.
- Cost effective
- Compatible with some CFL lamps



ECLIPSE STYLE GLASS




Colours Available:


All light kits are available in most motor colours ~ White, White Birch, Black, Brushed Chrome, Polished Brass, Antique Brass, Burnt Copper and Stainless Steel.

Packaging Dimensions 17H x 25W x 25L Weight

1.5 kg

GX53M 14W Compact Fluorescent Light






A Base

- B Lamp Assembly Low heat
- C Tube
- Low wattage
- High light output
- Liquid mercury free
- Colour-Warm white/Cool white colour temperatures available
- 12000 hour life span
- 2700k or 3000k

Flat 6, 26W Fluorescent Lamp



- High Efficiency (EEI=A2)
- High light output
- Liquid mercury free
- Low heat
- Fewer shadows visible
- Dimmable on certain fan models; ecO² & Ice Range (with Model 089 FLDR)
- 4100k

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au

[^] All light kits must be installed by a licensed electrician. For further information about correct installation procedures, please see www.hunterpacific.com.au